


# LEUPOLD® GOLDEN RING® ULTIMATE SLAM™ 2-7 x 33mm RIFLESCOPES



SABR™ (Sabot Ballistics Reticle™)



Leupold's all new UltimateSlam™ rifle scope is the ideal combination of flexibility, accuracy, and durability for today's modern muzzleloaders. Using a rugged and incredibly precise electroforming process, its advanced SABR™ (Sabot Ballistics Reticle™) reticle provides precise and distinct hold points for 50, 100, 150, 200, 250, and 300 yards, accurately allowing for sabots with 2-pellet or 3-pellet loads. The range estimation feature instantly tells you if that trophy whitetail is closer or farther than 200 yards. Leupold's

Standard Multicoat Lens System, 1/4 - MOA finger-click adjustments and waterproof, shockproof and fog proof construction combine to deliver the rugged reliability and crisp sight picture expected from Leupold in any hunting conditions. And, like all Golden Ring Scopes, the Ultimate-Slam provides the last word in lab and field tested ruggedness for a lifetime of dependability in the field. Protected by Leupold's industry leading Golden Ring Lifetime Warranty.

## LEUPOLD® GOLDEN RING® ULTIMATE SLAM™ 2-7x33mm RIFLESCOPES SPECIFICATIONS

Reticle	SABR™	
Item Number & Finish	65475 (Matte)	65510 (Silver)
Lens Coating	Standard Multicoat Lens System	
Adjustment Markings	1/4 MOA Finger Click	
Maintube Diameter	1"	
Special Features	SABR Reticle™, 2 and 3 pellet ballistics, range estimation	
Environmental Protection	Waterproof/Fog Proof	
Eyepiece Design	Classic Lockable Eyepiece	
Actual Magnification	2.5x – 6.5x	
Linear Field of View (ft @ 100yd)	17.3 feet at high magnification, 43.2 feet at low magnification	
Linear Field of View (ft @ 100m)	5.8 meters at high magnification, 14.4 meters at low magnification	
Exit Pupil	16.5 – 4.7	
Weight (ounces)	10.5	
Weight (grams)	297.7	
Length (in)	10.8	
Length (cm)	27.4	
Mounting Space (in)	5.2	
Mounting Space (cm)	13.2	
Objective Aperture (mm)	33	
Eye Relief (in)	4.2 – 3.7	
Eye Relief (mm)	106.0 – 94.0	
Elevation Adjustment Range (MOA)	65	
Windage Adjustment Range (MOA)	65	



**LEUPOLD®**  
AMERICA'S OPTICS AUTHORITY®