



LEUPOLD

SPOTTING SCOPE OWNER'S MANUAL

Complete Setup & Operating Instructions

REGISTER YOUR PRODUCT AT: [LEUPOLD.COM/PRODUCT-REGISTRATION](https://leupold.com/product-registration)

LET'S GET STARTED

Scan the QR code for additional Leupold Spotting Scope Support



Spotting Scope overview
Installing Form-Fit eyecups
Spotting Scope maintenance and troubleshooting

PARTS OF THE SPOTTING SCOPE



- 1 Objective Lens/Lens Shade
- 2 Tripod Adapter Foot
- 3 Eyepiece Lens/Eyecup
- 4 Power Selector
- 5 Focus Adjustment
- 6 Tripod Body Adjustment Ring/Locking Screw

Thank you for choosing a Leupold® spotting scope. We've worked tirelessly to make sure it will provide you with a lifetime of performance.

USING LEUPOLD SPOTTING SCOPES

Leupold spotting scopes are designed for ease of use, featuring twist-up eyecups that accommodate both eyeglass wearers and those without glasses. To adjust the eyecup for use with glasses, simply twist it to its lowest position. To extend it for unaided viewing, grasp the edge of the eyecup and twist it away from the spotting scope. Some models even include interchangeable Form-Fit eyecups for an enhanced viewing experience.

CHANGING MAGNIFICATION

Magnification levels of Leupold spotting scopes can be changed by rotating the power selector located in front of the eyepiece. While viewing through the scope, turning the power selector clockwise increases magnification, while turning it counterclockwise decreases magnification.

FOCUSING

1. Place the eyecup in the desired position.
2. View the object you desire to observe through the spotting scope.
3. Adjust the magnification level as desired.
4. Turn the focus adjustment until the image of the object being viewed is seen as crisp and sharp.

USING A TRIPOD

Leupold spotting scopes feature a 1/4-20 thread tripod adapter, compatible with the standard 1/4-20 mounting screw used on most tripods. They also feature an integrated Arca-Swiss tripod adapter, allowing for quick and secure mounting to any Arca-Swiss compatible head.

ADJUST THE VIEWING ANGLE

The tripod mounting ring allows you to rotate the spotting scope body to enhance your viewing experience.

- Turn the mounting ring adjustment screw counterclockwise to loosen the mounting ring.
- Rotate the spotting scope body to a comfortable viewing angle.
- Turn the adjustment screw clockwise to secure the spotting scope's position.

MAINTENANCE

SEALS:

Leupold spotting scopes are sealed from within by several methods, including O-rings and special compounds. All seals are permanent and require no maintenance.

LENSES:

Should the lenses of the spotting scope become dirty, clean them as you would any fine camera lens.

1. Use a lens brush to remove dust.
2. Fingerprints that cannot be removed by brushing can be removed with a good grade of glass cleaner. When wiping the lens, use a soft cloth and wipe from the center of the lens outward.

WARRANTY SERVICE

Should service ever become necessary, this spotting scope is backed by the Leupold Full Lifetime Guarantee. All service work is performed by the Leupold Product Service department in Beaverton, Oregon.

LEUPOLD PRODUCT SERVICE

If your Leupold spotting scope fails to perform in any way, you may return it directly to the factory (or one of our international service centers) for service. To return a product for service from within the U.S. follow these shipping instructions:

1. Remove accessories from the spotting scope.
2. Record the serial number of the spotting scope and keep it for your records.
3. Visit leupold.com/return-warranty-services and follow the instructions there to start the warranty process.
When shipping the product, include the packing slip that will be provided.
4. Pack the spotting scope in its original box (if you have it), as this is the safest shipping container.
Wrap the package securely using filament strapping tape on the outside.
5. Ship the spotting scope by a traceable parcel or mail service (insured, if possible) to one of the following addresses:

IN THE UNITED STATES:

BY PARCEL SERVICE:

Leupold Product Service
14400 NW Greenbrier Parkway
Beaverton, OR 97006-5791 USA

BY MAIL:

Leupold Product Service
P.O. Box 688
Beaverton, OR 97075-0688 USA

We can also be contacted through our website at leupold.com

FOR SERVICE OUTSIDE THE UNITED STATES:

Canada: Korth Group Ltd., 64186-393 Loop East, Okotoks, AB T1S 0L1, Canada

Australia: Nioa, PO Box 191, Pinkenba, Qld 4008 Australia (for items originating from Australia, New Zealand, New Caledonia and Japan)

South Africa: Formalito, 1019 Pretorius Ave., Lyttelton Manor, 0157, South Africa

THE LEUPOLD LIFETIME GUARANTEE

Anyone can offer you a lifetime warranty, but guaranteeing performance takes serious dedication and craftsmanship. From our Beaverton, Oregon factory to the wilderness, the battlefield, and everywhere in between, we won't let you down. If your Leupold scope, sight, binocular, or spotting scope doesn't perform, we will repair or replace it for free – whether you're the original owner or not – forever.

For complete details visit leupold.com/support/lifetime-guarantee

For patent information, visit leupold.com/patents

We reserve the right to make design and/or material modifications without prior notice.
Copyright © 2024 Leupold & Stevens, Inc. All rights reserved.



[LEUPOLD.COM](https://leupold.com)

LEUPOLD & STEVENS INC.

P.O. BOX 688	14400 NW GREENBRIER PARKWAY
BEAVERTON, OR 97075-0688 U.S.A.	BEAVERTON, OR 97006-5790 U.S.A.
1(800) LEUPOLD (538-7653)	(503) 526-1400

BE RELENTLESS.